


SPECIFICATION :-

| | | |
|----|-----------------------|------------------------|
| 1. | ORP RANGE | ±2000 mV |
| 2. | OPERATING TEMPERATURE | -5 TO 80°C |
| 3. | PRESSURE | UP TO 6 BAR AT 25°C |
| 4. | DIAPHRAGM, NOS. | CERAMIC, 2 |
| 5. | NO. OF JUNCTIONS/TYPE | DOUBLE (PAPER CERAMIC) |
| 6. | REFERENCE SYSTEM | SREF+ (CARTRIDGE) |
| 7. | SHIPPING CAP SOLUTION | 4M Kcl & 4pH (50/50) |
| 8. | REFERENCE ELECTROLYTE | HGel+ |

| | | |
|-----|-------------------|--|
| 9. | SHAPE OF MEMBRANE | PLATINIUM SPIRAL (17 AS STANDARD SUPPLY) |
| 10. | DIAMETER | 12 mm |
| 11. | SHAFT LENGTH | 120 mm |
| 12. | SHAFT MATERIAL | POLYCARBONATE (PLASTIC) |

ALL DIMENSIONS ARE IN MM

| | | | |
|----------|---------|---|-------------------|
| DRN. | KKS | CODE ARTICLE : MPTE0212 | |
| CHKD. | Pawan |  | www.ccei-pool.com |
| APPD. | | | |
| DATE | 19.6.26 | | |
| SCALE :- | 1:1 | DRG. NO. | REV. 0 |